



DB9M	DB9F
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
SHIELD	SHIELD

⑥	THUMB SCREW: #4-40UNC
⑤	OUTER MOLD: PVC 45P COLOR BEIGE
④	INNER MOLD: PVC 65P
③	CONNECTOR: DB9 MALE SOLDER TYPE INSULATION:BLUE
②	CONNECTOR: DB9 FEMALE SOLDER TYPE INSULATION:BLUE
①	CABLE: NOUL 28AWG*9C+AD O.D:5.0MM PVC JACKET COLOR BEIGE(CS-B02)
NO.	DESCRIPTION

**ELECTRICAL TEST:**  
 1.100% SHORT,OPEN,MISWIRE TEST  
 2.CONTACTOR RESISTANCE: 2 Ohm (MAX.)  
 3.INSULATION RESISTANCE: 5M Ohm(MIN.)



Scale	1:1						Name	Item No. <b>AK180-10</b>
TOLERANCE					Drawn	11.15.11	Chappell	
X.X	±0.40				Approved			Title Extension Cable M-F 9 Pin, 10 Meters
X.XX	±0.25							Drawing No.
X.XXX	±0.15							<b>rev00</b>
Angle	±3°							Replace
								Sheet
		Modification	Date	Name				