

A	1	2	3	4	5	6	7	A																																		
B								B																																		
C								C																																		
D	<p>Order code: A-MCUP-80xxx    Order color: Grey  Order code: A-MCUP-80xxx/x</p> <p>Order color:  R: Red  Y: Yellow  G: Green  B: Blue  ② BK:Black</p> <p>③ Tolerance</p> <table border="1" data-bbox="821 929 981 1153"> <thead> <tr> <th>Length Code</th> <th>Length (M)</th> </tr> </thead> <tbody> <tr><td>005</td><td>0.5</td></tr> <tr><td>010</td><td>1</td></tr> <tr><td>020</td><td>2</td></tr> <tr><td>030</td><td>3</td></tr> <tr><td>050</td><td>5</td></tr> <tr><td>070</td><td>7</td></tr> <tr><td>100</td><td>10</td></tr> <tr><td>150</td><td>15</td></tr> <tr><td>200</td><td>20</td></tr> <tr><td>300</td><td>30</td></tr> </tbody> </table> <table border="1" data-bbox="662 1153 821 1377"> <thead> <tr> <th>Length (M)</th> <th>Max-M</th> <th>Min-M</th> </tr> </thead> <tbody> <tr> <td>0.5</td> <td>+0.03</td> <td>-0.025</td> </tr> <tr> <td>1</td> <td>+0.04</td> <td>-0.035</td> </tr> <tr> <td>L≥2</td> <td>+L x 3%</td> <td>-L x 3%</td> </tr> </tbody> </table> <p>③ Tolerance</p>							Length Code	Length (M)	005	0.5	010	1	020	2	030	3	050	5	070	7	100	10	150	15	200	20	300	30	Length (M)	Max-M	Min-M	0.5	+0.03	-0.025	1	+0.04	-0.035	L≥2	+L x 3%	-L x 3%	D
Length Code	Length (M)																																									
005	0.5																																									
010	1																																									
020	2																																									
030	3																																									
050	5																																									
070	7																																									
100	10																																									
150	15																																									
200	20																																									
300	30																																									
Length (M)	Max-M	Min-M																																								
0.5	+0.03	-0.025																																								
1	+0.04	-0.035																																								
L≥2	+L x 3%	-L x 3%																																								
E	<p>PIN OUT</p> <table border="1" data-bbox="662 884 805 1131"> <thead> <tr> <th>CN1</th> <th>WIRE COLOR</th> <th>CN2</th> </tr> </thead> <tbody> <tr><td>1</td><td>ORANGE/WHITE</td><td>1</td></tr> <tr><td>2</td><td>ORANGE</td><td>2</td></tr> <tr><td>3</td><td>GREEN/WHITE</td><td>3</td></tr> <tr><td>4</td><td>GREEN</td><td>4</td></tr> <tr><td>5</td><td>BLUE</td><td>5</td></tr> <tr><td>6</td><td>BLUE/WHITE</td><td>6</td></tr> <tr><td>7</td><td>BROWN/WHITE</td><td>7</td></tr> <tr><td>8</td><td>BROWN</td><td>8</td></tr> </tbody> </table>							CN1	WIRE COLOR	CN2	1	ORANGE/WHITE	1	2	ORANGE	2	3	GREEN/WHITE	3	4	GREEN	4	5	BLUE	5	6	BLUE/WHITE	6	7	BROWN/WHITE	7	8	BROWN	8	E							
CN1	WIRE COLOR	CN2																																								
1	ORANGE/WHITE	1																																								
2	ORANGE	2																																								
3	GREEN/WHITE	3																																								
4	GREEN	4																																								
5	BLUE	5																																								
6	BLUE/WHITE	6																																								
7	BROWN/WHITE	7																																								
8	BROWN	8																																								
F	<p><b>Electrical</b>  Open/short/intermittence: 100%  The operating temperature: -20°C~+60°C  The storage temperature: -20°C~+60°C</p> <table border="1" data-bbox="454 638 614 862"> <thead> <tr> <th>NO.</th> <th>NAME.</th> <th>QTTY</th> <th>DATE</th> <th>NAME</th> </tr> </thead> <tbody> <tr> <td>③</td> <td>Molding PVC</td> <td>2</td> <td></td> <td></td> </tr> <tr> <td>②</td> <td>RJ45 CONN</td> <td>2</td> <td>25.05.2014</td> <td>Joanna</td> </tr> <tr> <td>①</td> <td>CABLE</td> <td>1</td> <td>23.08.2018</td> <td>Amy</td> </tr> </tbody> </table> <p>SPECIFICATION</p>							NO.	NAME.	QTTY	DATE	NAME	③	Molding PVC	2			②	RJ45 CONN	2	25.05.2014	Joanna	①	CABLE	1	23.08.2018	Amy	F														
NO.	NAME.	QTTY	DATE	NAME																																						
③	Molding PVC	2																																								
②	RJ45 CONN	2	25.05.2014	Joanna																																						
①	CABLE	1	23.08.2018	Amy																																						
G	<p><b>ROHS compliant</b>  Unit: mm</p> <table border="1" data-bbox="279 392 438 616"> <thead> <tr> <th>Scale</th> <th>FREE</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> </tr> <tr> <td>Angle</td> <td>TOL</td> </tr> </tbody> </table> <table border="1" data-bbox="279 616 438 840"> <thead> <tr> <th>Id.</th> <th>Modification</th> <th>Date</th> <th>Name</th> </tr> </thead> <tbody> <tr> <td>③</td> <td>Clarify the tolerance</td> <td>23.08.2018</td> <td>Segal</td> </tr> <tr> <td>②</td> <td>Add the new P/N for black outer jacket</td> <td>01.11.2017</td> <td>Winnie</td> </tr> <tr> <td>①</td> <td>Add the product type of length and color</td> <td>04.08.2017</td> <td>Fred</td> </tr> <tr> <td>①</td> <td>Drawn</td> <td>25.05.2014</td> <td>Joanna</td> </tr> </tbody> </table> <p>Customer-No.    ASSMANN WSW-No.    A-MCUP-80xxx/x  Drawing-No.    ASS 7407 CA    rev03</p>							Scale	FREE	TOLERANCE		DIM	TOL	Angle	TOL	Id.	Modification	Date	Name	③	Clarify the tolerance	23.08.2018	Segal	②	Add the new P/N for black outer jacket	01.11.2017	Winnie	①	Add the product type of length and color	04.08.2017	Fred	①	Drawn	25.05.2014	Joanna	G						
Scale	FREE																																									
TOLERANCE																																										
DIM	TOL																																									
Angle	TOL																																									
Id.	Modification	Date	Name																																							
③	Clarify the tolerance	23.08.2018	Segal																																							
②	Add the new P/N for black outer jacket	01.11.2017	Winnie																																							
①	Add the product type of length and color	04.08.2017	Fred																																							
①	Drawn	25.05.2014	Joanna																																							
H	<p>Replace    ASSMANN components</p>							H																																		
1	2	3	4	5	6	7	H	CAB0742																																		