







Keystone module, design compatible, CAT 5E, unshielded



NOTES:

General information:

1. Tool-free Installation
2. Unshielded
3. Transmsslon Properties: CAT 5E
4. Area of Application: 100MHz, 10-100MBit
5. Standard: ISO/IEC 11801 ; TIA/EIA 568-C

ELECTRICAL:

1. VOLTAGE RATING: 125VAC.
2. CURRENT RATING: 1.5AMP.
3. CONTACT RESISTANCE: 100mΩ MAX.
4. INSULATION RESISTANCE: 1000 MΩ MIN. @ 500 VDC.
5. DIELECTRIC STRENGTH: 750 VAC 60Hz, 1 MIN.
6. CONFORM TO ANSI/TIA/EIA-568 B.2-1

MECHANICAL:

1. HOUSING MATERIAL: PC UL94V-0.
2. INSERT MATERIAL: PBT+30%GF, UL94V-0.
3. PCB MATERIAL: FR-4 THICKNESS 1.6mm.
4. CONTACT MATERIAL: PHOSPHOR BRONZE
STAMP PIN t=0.35mm.
50u" selective gold plated
5. IDC CONTACT MATERIAL: PHOSPHOR BRONZE t=0.50mm,
WITH NICKEL PLATING.
6. WIRE: #24~26 AWG.

ENVIRONMENTAL:

1. STORAGE: -40°C TO +85°C.
 - ① 2. OPERATION: -40°C TO +85°C.
- CONFORMING TO TIA/EIA 568B
MATES WITH MODULAR PLUG CONFORMING TO TIA-1096-A.
Package: 1pcs/PE bag ; 20pcs/box

WSW Order code A-KEY-8-EG-GIB-WI x1

Housing color option
B: Blue
W: White
K: Black

RoHS compliant
Unit: mm

Scale	Free						Date	Name	Customer-No.	
TOLERANCE						Drawn	12.06.2018	Xavier	ASSMANN WSW-No. A-KEY-8-EG-GIB-WI x1	
X.X	±0.20					Approved	17.12.2018	Amy		
X.XX	±0.15									
X.XXX	±0.10									
DIM	TOL	①	Update the notes	17.12.2018	Segal				Drawing-No.	
		②	Drawn	16.05.2018	Xavier				ASS 7955 CO	rev01
Angle	±5°	Id.	Modification	Date	Name				Replace	Sheet