




1	2	3	4	5	6	7																																																																																																																														
A	<table border="1"> <tr> <td colspan="2">Wire Spec</td> <td colspan="4">UL2725 (7/0.127TC*1P+D+AL+MYLAR)*2+ 7/0.127T*1P+7/0.20T*2C+F+A+DB</td> </tr> <tr> <td colspan="2">Cores</td> <td>2P</td> <td>1P</td> <td colspan="2">2C</td> </tr> <tr> <td colspan="2">AWG</td> <td>28AWG</td> <td>28AWG</td> <td colspan="2">24AWG</td> </tr> <tr> <td colspan="2">Material</td> <td>Tinned Copper</td> <td>Tinned Copper</td> <td colspan="2">Tinned Copper</td> </tr> <tr> <td colspan="2">Construction</td> <td>7/0.127±0.004mm</td> <td>7/0.127±0.004mm</td> <td colspan="2">7/0.2±0.004mm</td> </tr> <tr> <td colspan="2">O.D</td> <td>0.38mm (REF)</td> <td>0.38mm (REF)</td> <td colspan="2">0.60mm (REF)</td> </tr> <tr> <td colspan="2">Thickness</td> <td>0.26mm (REF)</td> <td>0.23mm (REF)</td> <td colspan="2">0.25mm (REF)</td> </tr> <tr> <td colspan="2">O.D</td> <td>0.90±0.05mm</td> <td>0.84±0.05mm</td> <td colspan="2">1.10±0.05mm</td> </tr> <tr> <td colspan="2">Color</td> <td>Yellow,Blue,Orange,Purple</td> <td>WHITE, GREEN</td> <td colspan="2">RED, BLACK</td> </tr> <tr> <td colspan="2">Material</td> <td>Foamed PE</td> <td>HDPE</td> <td colspan="2">SR-PVC</td> </tr> <tr> <td colspan="2">Insulation</td> <td colspan="4">FILLER</td> </tr> <tr> <td colspan="2">Filler</td> <td colspan="4"></td> </tr> <tr> <td colspan="2">Braid</td> <td colspan="4">AL-MG</td> </tr> <tr> <td colspan="2">Construction</td> <td colspan="4">16/6/0.12mm</td> </tr> <tr> <td colspan="2">Shield</td> <td colspan="4">AL foil Color :Blue</td> </tr> <tr> <td colspan="2">Material</td> <td colspan="4">MYLAR White</td> </tr> <tr> <td colspan="2">Construction</td> <td colspan="4">Tinned Copper</td> </tr> <tr> <td colspan="2">Material</td> <td colspan="4">80°C PVC 80P</td> </tr> <tr> <td colspan="2">O.D</td> <td colspan="4">5.5±0.20mm</td> </tr> <tr> <td colspan="2">Color</td> <td colspan="4">Black</td> </tr> <tr> <td colspan="2">Font Color</td> <td colspan="4">White</td> </tr> </table> <p>② Print: 9U AWM STYLE 2725 80°C 30V 28AWG/3P 80°C 30V FT1 24AWG/2C ---- C AWM I/II A 80°C 30V FT1 USB CABLE</p>						Wire Spec		UL2725 (7/0.127TC*1P+D+AL+MYLAR)*2+ 7/0.127T*1P+7/0.20T*2C+F+A+DB				Cores		2P	1P	2C		AWG		28AWG	28AWG	24AWG		Material		Tinned Copper	Tinned Copper	Tinned Copper		Construction		7/0.127±0.004mm	7/0.127±0.004mm	7/0.2±0.004mm		O.D		0.38mm (REF)	0.38mm (REF)	0.60mm (REF)		Thickness		0.26mm (REF)	0.23mm (REF)	0.25mm (REF)		O.D		0.90±0.05mm	0.84±0.05mm	1.10±0.05mm		Color		Yellow,Blue,Orange,Purple	WHITE, GREEN	RED, BLACK		Material		Foamed PE	HDPE	SR-PVC		Insulation		FILLER				Filler						Braid		AL-MG				Construction		16/6/0.12mm				Shield		AL foil Color :Blue				Material		MYLAR White				Construction		Tinned Copper				Material		80°C PVC 80P				O.D		5.5±0.20mm				Color		Black				Font Color		White			
Wire Spec		UL2725 (7/0.127TC*1P+D+AL+MYLAR)*2+ 7/0.127T*1P+7/0.20T*2C+F+A+DB																																																																																																																																		
Cores		2P	1P	2C																																																																																																																																
AWG		28AWG	28AWG	24AWG																																																																																																																																
Material		Tinned Copper	Tinned Copper	Tinned Copper																																																																																																																																
Construction		7/0.127±0.004mm	7/0.127±0.004mm	7/0.2±0.004mm																																																																																																																																
O.D		0.38mm (REF)	0.38mm (REF)	0.60mm (REF)																																																																																																																																
Thickness		0.26mm (REF)	0.23mm (REF)	0.25mm (REF)																																																																																																																																
O.D		0.90±0.05mm	0.84±0.05mm	1.10±0.05mm																																																																																																																																
Color		Yellow,Blue,Orange,Purple	WHITE, GREEN	RED, BLACK																																																																																																																																
Material		Foamed PE	HDPE	SR-PVC																																																																																																																																
Insulation		FILLER																																																																																																																																		
Filler																																																																																																																																				
Braid		AL-MG																																																																																																																																		
Construction		16/6/0.12mm																																																																																																																																		
Shield		AL foil Color :Blue																																																																																																																																		
Material		MYLAR White																																																																																																																																		
Construction		Tinned Copper																																																																																																																																		
Material		80°C PVC 80P																																																																																																																																		
O.D		5.5±0.20mm																																																																																																																																		
Color		Black																																																																																																																																		
Font Color		White																																																																																																																																		
B	 <p>① Wire color assignment</p> 																																																																																																																																			
C	 <p>Packing: 305M/Reel</p>																																																																																																																																			
D	<table border="1"> <tr> <td>Scale</td> <td>Free</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="2">TOLERANCE</td> <td>④</td> <td>Add the packing information</td> <td>18.10.2018</td> <td>Segal</td> <td>Drawn</td> <td>26.01.2018</td> <td>Winnie</td> </tr> <tr> <td></td> <td></td> <td>③</td> <td>Correct Brown to Purple</td> <td>06.09.2018</td> <td>Xavier</td> <td>Approved</td> <td>18.10.2018</td> <td>Winnie</td> </tr> <tr> <td></td> <td></td> <td>②</td> <td>Update</td> <td>29.08.2018</td> <td>Xavier</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>①</td> <td>Update</td> <td>07.08.2018</td> <td>Xavier</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>①</td> <td>Drawn</td> <td>26.01.2018</td> <td>Winnie</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> <td></td> <td></td> </tr> </table>						Scale	Free						TOLERANCE		④	Add the packing information	18.10.2018	Segal	Drawn	26.01.2018	Winnie			③	Correct Brown to Purple	06.09.2018	Xavier	Approved	18.10.2018	Winnie			②	Update	29.08.2018	Xavier						①	Update	07.08.2018	Xavier						①	Drawn	26.01.2018	Winnie				Angle	TOL	Id.	Modification	Date	Name																																																																				
Scale	Free																																																																																																																																			
TOLERANCE		④	Add the packing information	18.10.2018	Segal	Drawn	26.01.2018	Winnie																																																																																																																												
		③	Correct Brown to Purple	06.09.2018	Xavier	Approved	18.10.2018	Winnie																																																																																																																												
		②	Update	29.08.2018	Xavier																																																																																																																															
		①	Update	07.08.2018	Xavier																																																																																																																															
		①	Drawn	26.01.2018	Winnie																																																																																																																															
Angle	TOL	Id.	Modification	Date	Name																																																																																																																															
G	<p>Customer-No. ASSMANN WSW-No. KAB 6641</p> <p>Drawing-No. ASS 8186 CA rev04</p> <p>Replace Sheet 1 / 1</p>																																																																																																																																			
H	<p>ASSMANN WSW components</p>																																																																																																																																			

ROHS compliant
Unit:mm

1

2

3

4

5

6

7

CA60844