



- NOTES:**
Material:
 1. SVT 3x18AWG(0.824MM²) VW-1, 60°C 300V.
 2. Jacket Color: Black.
 3. E-Green, L-Black, N-White.

- Electrical Test:**
 1. 100% Open & Short Testing.
 2. Insulation Resistance: 100MΩ(Min).
 3. Voltage: 500V DC/1Min.

| WSW P/N | L(mm) |
|----------------|---------|
| AK500-RA-6-0.5 | 500±50 |
| AK500-RA-6-1 | 1000±50 |
| AK500-RA-6-1.5 | 1500±50 |
| AK500-RA-6-2 | 2000±50 |

RoHS compliant
 Unit: mm

| Scale | Free |
|-----------|------|
| TOLERANCE | |
| DIM | TOL |
| Angle | TOL |

| Id. | Modification | Date | Name |
|-----|--------------|------------|-------|
| ① | Drawn | 02.11.2018 | Segal |

| Date | Name |
|------------|-------|
| 02.11.2018 | Segal |
| 02.11.2018 | Amy |

| Customer-No. | Drawing-No. | Replace |
|-----------------|--------------|-------------|
| ASSMANN WSW-No. | AK500-RA-6-X | ASS 8404 CA |
| | | rev00 |



| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | A |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | H |