



REMARK:

1.CABLE:

NON-UL 4C 28AWG(7/0.127)TINNED COPPER INSULATION:PVC
+AL/MY JACKET PVC COLOR:BEIGE(NK-A03)OD:3.5±0.15mm Δ

2.CONNECTORS:

P1: MD 6P FEMALE, GOLD FLASH CONTACT, NICKEL PLATED SHELL
P2: HOUSING PITCH:2.54-2*5POS,COLOR:BLACK.

3.HOOD:P1 MOLDED TYPE,45P PVC COLOR:BEIGE(NK-A03)

4.TEST REQUEST:

<1> 100% OPEN SHORT & MIS WIRE TEST

<2>.CONTACT RESISTANCE 3 OHM MAX

<3>.INSULATION RESISTANCE 20M OHM MIN

Δ 5.PACKING:SEE P-0039 REV.C PACKING DRAWING+EAN CODE:4016032051497

Δ (BINDING SIZE MUST BE SMALLER THAN BLISTER)

Δ 6.BLISTER SIZE:DB VP2

PIN OUT

P1	P2
1	4
3	1
4	6
5	9



ITEM NO	AK-PS2-R
TITLE	PS/2 Internal Cable

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
© Copyright 2008 by Assmann Electronic Components
All International Rights Reserved