



- NOTES:**
- A. Material:
    1. Housing: PA66 UL 94V-0 Color : Black
    2. Terminal: COPPER ALLOY; TIN PLATED
  - B. Electrical Characteristics:
    1. Rating: 15A, 250V ~ UL, CUL
    - 10A, 250V ~ VDE, SEMKO, CCC
    2. Electric Strength: AC 2,000 V FOR ONE MINUTE
    3. Insulation Resistance: 100MΩ MIN. AT 500V DC
  - C. Approvals:
    - UL, CUL, VDE, SEMKO, CCC

**RoHS compliant**

Scale	1:1
<b>TOLERANCE</b>	
0-10	±0.1
10-30	±0.3
30-100	±0.5
<b>DIM</b>	<b>TOL</b>
①	Drawn
②	Change of plant
③	Add the panel of thickness
<b>UNIT</b>	mm

Id.	Modification	Date	Name
①	Drawn	08.07.2009	Dean
②	Change of plant	18.12.2012	Winnie
③	Add the panel of thickness	19.10.2016	Winnie

1	2	3	4	5	6	7
A						
B						
C						
D						
E						
F						
G						
H						



ASSMANN WSW-No. A-KGS-S/T2

Customer-No.

ASSMANN WSW-No. A-KGS-S/T2

ASS 0889N CO rev03

Drawing-No.

SHEET