



NOTES:

- 1.ENVIRONMENTAL:
Temperature Range : -20°C To +80°C
- 2.MATERIAL:
Insulator Material:Glass-filled thermoplastic Natural,UL94V-0
Contact Material:Phosphor Bronze
Shell :SPCC or ZINC Alloy, Nickel Over Cu Plated
Board lock : Brass Tin Plated
- 3.ELECTRICAL
Rating : 1.5A @ 40V AC (ms)
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ min
Withstand Voltage: 500V AC(ms)
- 4.MECHANICAL
Mating force : 10 LB.(4.5Kg) Max
Unmating Force :2.2LB.(1Kg) Min .8LB.(4Kg)Max.

RoHS compliant

Scale	1:1						Date	Name	Customer-No.
TOLERANCE						Drawn	29.12.2008	Dean	ASSMANN WSW-No. A-DVI-29I
X.	±0.38					Approved	29.12.2008	Hellwig	
X.X	±0.25								
X.XX	±0.13								
DIM	TOL								Drawing-No.
X.°	±3°								ASS 3272 CO
X.X°	±1.0°	①	Drawn	29.12.2008	Dean			rev01	
Angle	TOL	Id.	Modification	Date	Name			Replace	Sheet

