



MARKING:



MARKING:



- NOTES:
- 1.CABLE: VDE APPROVED H05VV-F 3G0.75MM2 JACKET COLOR: BLACK  
CABLE MUST PRINT:<VDE> H05VV-F 3G0.75MM2
  - 2.CONNECTOR:  
P1 : CEE 7/7 3P/M, CRIMP, NICKEL PLATED TERMINAL  
P2 : IEC C13, CRIMP, NICKEL PLATED TERMINAL
  - 3.HOOD: MOLDED TYPE,PVC 45P,COLOR:BLACK.
  - 4.PLUG INSERT: PBT, COLOR: WHITE
  - 5.ELECTRICLE TEST:  
(1)100% OPEN SHORT & MIS WIRE TEST.  
(2)CONTACT RESISTANCE 2 ohm Max .  
(3)INSULATION RESISTANCE 10M ohm Min .  
(4)HI-POT TEST:DC 300V/10ms

**RoHS compliant**  
Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	29.06.2009	Rale
X.	±X					Approved	19.08.2014	Amy
X.X	±X							
X.XX	±X	③	Update the WSW P/N	19.08.2014	Amy			
DIM	TOL	②	Update the drawing	25.06.2014	Amy			
X.°	±X°	①	Drawn	29.06.2009	Rale			
X.X°	±X°							
Angle	TOL	Id.	Modification	Date	Name			



Customer-No.		
ASSMANN WSW-No.		③AK-440102-018-S
Drawing-No.	ASS 3601 CA	rev03
Replace		Sheet