



NOTES:

- CABLE a: VDE APPROVED H05VV-F 3G 1.0MM2 JACKET COLOR: BLACK
CABLE MUST PRINT: <VDE> H05VV-F 3G 1.0 MM2
CABLE b: VDE APPROVED H05VV-F 3G 0.75MM2 JACKET COLOR: BLACK
CABLE MUST PRINT: <VDE> H05VV-F 3G 0.75MM2
- CONNECTOR:
P1 : CEE 7/7 Plug, R/A, CRIMP, NICKEL PLATED TERMINAL
P2 : IEC C13, CRIMP, NICKEL PLATED TERMINAL
- HOOD: MOLDED TYPE,PVC 45P,COLOR:BLACK.
- PLUG INSERT: PBT, COLOR: WHITE
- ELECTRICLE TEST:
(1)100% OPEN SHORT & MIS WIRE TEST.
(2)HIGH-POT: AC2500V,2S.
(3)SKIN HIGH-POT: AC 4500V, 2S
(4)LEAKAGE CURRENT: 1.0mA

Conductor		Insulation			Jacket		Overall Diameter
MM²	Construction	Diameter	Min.Thick	AVG.Thick	Min.Thick		
0.75	24/0.20mm	2.4±0.05mm	0.44mm	0.6mm	0.58mm	6.8 ± 0.1mm	
1.00	32/0.20mm	2.5± 0.05mm	0.44mm	0.6mm	0.58mm	7.0 ± 0.1mm	

RoHS compliant
Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	29.06.2009	Rale
X.	±X					Approved	19.08.2014	Amy
X.X	±X							
X.XX	±X	③	Update the WSW P/N	19.08.2014	Amy			
DIM	TOL	②	Update the drawing	25.06.2014	Amy			
X.°	±X°							
X.X°	±X°	①	Drawn	29.06.2009	Rale			
Angle	TOL	Id.	Modification	Date	Name			

ASSMANN WSW-No.		③AK-440401-017-S
Drawing-No.		
ASS 3602 CA		rev03
Replace		Sheet