

1

2

3

4

5

6

7

A

A

B

B

C

C

D

D

E

E

F

F

Technical drawings of the component including top, side, and detail views with dimensions and labels like POSN #1, POSN #34, POSN #35, POSN #68.

Section A-A and Section B-B views showing internal offsets and dimensions.

View D and View E showing contact details and dimensions.

View F and View G showing contact details and dimensions.

**SPECIFICATION**  
**MATERIAL**  
 Insulator: Thermal Plastic UL94V-0 ,Black  
 Contacts: Copper Alloy  
**CONTACT PLATING**  
 Underplate: 50u"~100u" Nickel  
 ② Contact Area: Gold flash (Selective Gold)  
 Solder Tails Area: 100u"~200u" Tin(Lead Free)  
**ELECTRICAL**  
 Operation Voltage: 100V AC Max.  
 Current Rating: 0.5 Amps Max.  
 Contact Resistance: 40 mohms Max.  
 Insulation Resistance: 1000 Mohms Min. @ 500 VDC  
 Dielectric Withstanding Voltage: 500 VAC / Minute  
 Temperature Range: -10°C To +70°C  
 ② Packing : Tray  
 A-PCMCIA-68-F-x-x-003  
 ② Offset dimension "X" 1=0.19mm  
 CONTACT AREA PLATING: ②  
 S=Gold Flash(Selective)

3D perspective view of the component.

**RoHS compliant**

Scale	1:1					Date	Name	Customer-No.
TOLERANCE						Drawn	11.08.2009	Dean
X.	±0.5					Approved	11.08.2009	Hellwig
X.X	±0.3							
X.XX	±0.2							
DIM	TOL	②	Update	18.06.2019	Xavier			
Angle	±5°	①	Drawn	11.08.2009	Dean			
Angle	TOL	Id.	Modification	Date	Name			

ASSMANN WSW-No.  
**A-PCMCIA-68-F-x-x-003**  
 Drawing-No.  
**ASS 3646 CO** rev02  
 Replace SHEET 1/1

1

2

3

4

5

6

7

SV1694