



Notes:

Ⓞ Important Dimension To Check

Waterproof Rate: IP67

LED Holder: Copper Alloy, Nickel Plating

LED Spec:

∅3mm, Super Bright, Red/Green, Bi-Color LED

Lens Color: Water Clear

Forward Voltage: Red Typ. 2.05V

Green Typ. 3.4V

Forward Current: Red Typ. 35mA

Green Typ. 20mA

Luminous Intensity: Red Typ. 1000 (Mcd)

Green Typ. 2000 (Mcd)

Reverse Voltage: DC 5V

Operating Temperature: -30~+80°C

O-Ring: Silicone, Gray

Screw Nut: Copper Alloy, Nickel Plating

For Panel Thickness 6.5 max.

**RoHS compliant**

Scale	Free						Date	Name	Customer-No.
TOLERANCE							Drawn	06.03.2014	Winnie
.X	±0.40						Approved	22.02.2017	Winnie
.XX	±0.25								
.XXX	±0.15								
Angle	±3°	①	Update the dimension	22.07.2016	Winnie				
		Ⓞ	Drawn	06.03.2014	Winnie				
		Id.	Modification	Date	Name				

Customer-No.	
ASSMANN WSW-No. A-LED8-1AAAS-MR7-1	
Drawing-No.	rev01
<b>ASS 6223 CO</b>	
Replace	Sheet

