



DIM	Long	Short
L	22.10	18.70
L1	14.60	10.60

No. of POSITION	DIM.A	DIM.B	DIM.C	DIM.D
6	15.281	12.42	5.08	2.30
8	17.82	14.96	7.62	2.30
10	20.36	17.50	10.16	5.00
12	22.90	20.04	12.70	5.00
14	25.44	22.58	15.24	5.00
16	27.98	25.12	17.78	5.00
20	33.06	30.20	22.86	5.00
24	38.14	35.28	27.94	5.00
26	40.68	37.82	30.48	5.00
30	45.76	42.90	35.56	5.00
34	50.84	47.98	40.64	5.00
40	58.46	55.60	48.26	5.00
50	71.16	68.30	60.96	5.00
60	83.86	81.00	73.66	5.00
64	88.94	86.08	78.74	5.00

**RoHS compliant**  
Unit: mm

Scale	Free	Date	Name
TOLERANCE		08.08.2017	Winnie
X.X	±0.40		
X.XX	±0.25	25.01.2018	Winnie
X.XXX	±0.15		
Angle	±3°		
① Update the P/N & the latch on the drawing			
② Drawn			
③ Drawn			
④ Drawn			
⑤ Drawn			
⑥ Drawn			
⑦ Drawn			
⑧ Drawn			
⑨ Drawn			
⑩ Drawn			
⑪ Drawn			
⑫ Drawn			
⑬ Drawn			
⑭ Drawn			
⑮ Drawn			
⑯ Drawn			
⑰ Drawn			
⑱ Drawn			
⑲ Drawn			
⑳ Drawn			
㉑ Drawn			
㉒ Drawn			
㉓ Drawn			
㉔ Drawn			
㉕ Drawn			
㉖ Drawn			
㉗ Drawn			
㉘ Drawn			
㉙ Drawn			
㉚ Drawn			
㉛ Drawn			
㉜ Drawn			
㉝ Drawn			
㉞ Drawn			
㉟ Drawn			
㊱ Drawn			
㊲ Drawn			
㊳ Drawn			
㊴ Drawn			
㊵ Drawn			
㊶ Drawn			
㊷ Drawn			
㊸ Drawn			
㊹ Drawn			
㊺ Drawn			
㊻ Drawn			
㊼ Drawn			
㊽ Drawn			
㊾ Drawn			
㊿ Drawn			

Customer-No.	Date	Name
	08.08.2017	Winnie
	25.01.2018	Winnie

- NOTES:**
- MATERIAL**
1. Insulator Material: PA9T+30%G.F.(UL94V-0), Black
  2. Latch Material: PA9T+30%G.F.(UL94V-0), Black
  3. Contact Material : Brass
  4. Contact Plating : Gold Flash / Over Ni
  5. Fix Axle: Brass
  6. Fix Axle Plating: Ni
- ELECTRICAL**
1. Current Rating : 1.0AMP
  2. Withstand Voltage : 500V AC/minute
  3. Contact Resistance : 20mΩ max
  4. Insulation Resistance : 1000MΩ min
- ENVIRONMENTAL**
1. Operation Temperature: -40°C to +105°C
  2. Soldering Temperature: 255°C±5°C/5s±1s
  3. Packing : Tray
  4. No. of Contact : 06-64
  - Order Code: AWHW-254-xx-SP10 : Short Latch  
AWHW-254-xx-SP12 : Long Latch



Drawing-No. ASS 7744 CO rev01

Customer-No. AWHW-254-xx-SP10  
AWHW-254-xx-SP12

1	2	3	4	5	6	7
H	G	F	E	D	C	B
<p>Scale Free</p> <p>TOLERANCE</p> <p>X.X ±0.40</p> <p>X.XX ±0.25</p> <p>X.XXX ±0.15</p> <p>Angle ±3°</p>						
<p>① Update the P/N &amp; the latch on the drawing</p> <p>② Drawn</p> <p>③ Drawn</p> <p>④ Drawn</p> <p>⑤ Drawn</p> <p>⑥ Drawn</p> <p>⑦ Drawn</p> <p>⑧ Drawn</p> <p>⑨ Drawn</p> <p>⑩ Drawn</p> <p>⑪ Drawn</p> <p>⑫ Drawn</p> <p>⑬ Drawn</p> <p>⑭ Drawn</p> <p>⑮ Drawn</p> <p>⑯ Drawn</p> <p>⑰ Drawn</p> <p>⑱ Drawn</p> <p>⑲ Drawn</p> <p>⑳ Drawn</p> <p>㉑ Drawn</p> <p>㉒ Drawn</p> <p>㉓ Drawn</p> <p>㉔ Drawn</p> <p>㉕ Drawn</p> <p>㉖ Drawn</p> <p>㉗ Drawn</p> <p>㉘ Drawn</p> <p>㉙ Drawn</p> <p>㉚ Drawn</p> <p>㉛ Drawn</p> <p>㉜ Drawn</p> <p>㉝ Drawn</p> <p>㉞ Drawn</p> <p>㉟ Drawn</p> <p>㊱ Drawn</p> <p>㊲ Drawn</p> <p>㊳ Drawn</p> <p>㊴ Drawn</p> <p>㊵ Drawn</p> <p>㊶ Drawn</p> <p>㊷ Drawn</p> <p>㊸ Drawn</p> <p>㊹ Drawn</p> <p>㊺ Drawn</p> <p>㊻ Drawn</p> <p>㊼ Drawn</p> <p>㊽ Drawn</p> <p>㊾ Drawn</p> <p>㊿ Drawn</p>						
<p>ASSMANN WSW/ components</p> <p>Drawing-No. ASS 7744 CO rev01</p> <p>Customer-No. AWHW-254-xx-SP10 AWHW-254-xx-SP12</p>						
H	G	F	E	D	C	B