

1	2	3	4	5	6	7																																			
A	1000±20																																								
B																																									
C	<p>Conductor 26/0.254 BC</p> <p>Insulation Ø3.1±0.05mm 45P PVC UL 105°C (Black, White, Green)</p> <p>Jacketed Ø8.4±0.2mm Black 55P PVC UL 105°C</p>																																								
D	<p>Requirement:</p> <ol style="list-style-type: none"> 1. Dielectric voltage: between jacket and conductor 4200V/s 2. Insulation resistance: 2500V/s ; 0.5MA 3. Continuity of lead 100% OK ④ 4. Current Rating: 13A ⑤ 5. Voltage Rating: 125v 																																								
E	<p>Cable Printing :CY86: Wire marking:</p> <p>(UL) E218701 SJT 16AWGX3C 300V 105°C VW-1</p> <p>C(UL) TYPE SJT 3*1.31mm²(16AWG) 300V 105°C E218701 FT2</p>																																								
F	<table border="1"> <thead> <tr> <th>NO.</th> <th>SPECIFICATION</th> <th>QTTY</th> <th>Unit</th> </tr> </thead> <tbody> <tr> <td>③</td> <td>Head+ terminal ,Color:White</td> <td>1</td> <td>EA</td> </tr> <tr> <td>②</td> <td>C13, Color:black PVC 55P</td> <td>0.0245</td> <td>Kg</td> </tr> <tr> <td>①</td> <td>SJT 16AWGX3C 105°C,Color:black L=980mm</td> <td>1</td> <td>EA</td> </tr> </tbody> </table>						NO.	SPECIFICATION	QTTY	Unit	③	Head+ terminal ,Color:White	1	EA	②	C13, Color:black PVC 55P	0.0245	Kg	①	SJT 16AWGX3C 105°C,Color:black L=980mm	1	EA																			
NO.	SPECIFICATION	QTTY	Unit																																						
③	Head+ terminal ,Color:White	1	EA																																						
②	C13, Color:black PVC 55P	0.0245	Kg																																						
①	SJT 16AWGX3C 105°C,Color:black L=980mm	1	EA																																						
G	<p>Customer-No. ASSMANN WSW-No. A-PC0916-100027</p>																																								
H	<p>Drawing-No. ASS 7897 CA rev01</p> <p>Replace Sheet</p>																																								
<p style="text-align: center;">ROHS compliant</p> <p style="text-align: center;">Unit: mm</p> <table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th>Free</th> <th>Free</th> <th>Free</th> <th>Free</th> <th>Free</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>① Add the current rating&voltage</td> <td>13.03.2017</td> <td>Winnie</td> <td>Drawn</td> <td>22.02.2017</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>② Drawn</td> <td>22.02.2017</td> <td>Winnie</td> <td>Approved</td> <td>13.03.2017</td> </tr> <tr> <td></td> <td></td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> </tr> </tbody> </table> <p style="text-align: center;">ASSMANN components</p>							Scale	Free	Free	Free	Free	Free	Free	TOLERANCE							DIM	TOL	① Add the current rating&voltage	13.03.2017	Winnie	Drawn	22.02.2017	Angle	TOL	② Drawn	22.02.2017	Winnie	Approved	13.03.2017			Id.	Modification	Date	Name	
Scale	Free	Free	Free	Free	Free	Free																																			
TOLERANCE																																									
DIM	TOL	① Add the current rating&voltage	13.03.2017	Winnie	Drawn	22.02.2017																																			
Angle	TOL	② Drawn	22.02.2017	Winnie	Approved	13.03.2017																																			
		Id.	Modification	Date	Name																																				