

1	2	3	4	5	6	7																																			
A	5000±60																																								
B																																									
C	<p>Conductor 26/0.254 BC Insulation Ø3.1±0.05mm 45P PVC UL 105°C (Black, White, Green) Jacketed Ø8.4±0.2mm Black 55P PVC UL 105°C</p>																																								
D																																									
E	<p>Cable Printing :CY86: Wire marking: (UL) E218701 SJT 16AWGX3C 300V 105°C VW-1 C(UL) TYPE SJT 3*1.31mm²(16AWG) 300V 105°C E218701 FT2</p> <p>Requirement: 1. Dielectric voltage: between jacket and conductor 4200V/s 2. Insulation resistance: 2500V/s ; 0.5MA 3. Continuity of lead 100% OK ① 4. Current Rating: 13A ① 5. Voltage Rating:125v</p>																																								
F	<table border="1"> <tr> <td>③ Head+ terminal ,Color:White</td> <td>1</td> <td>EA</td> </tr> <tr> <td>② C13, Color:black PVC 55P</td> <td>0.0245</td> <td>Kg</td> </tr> <tr> <td>① SJT 16AWGX3C 105°C,Color:black L=4980mm</td> <td>1</td> <td>EA</td> </tr> </table> <p style="text-align: center;">SPECIFICATION</p>						③ Head+ terminal ,Color:White	1	EA	② C13, Color:black PVC 55P	0.0245	Kg	① SJT 16AWGX3C 105°C,Color:black L=4980mm	1	EA																										
③ Head+ terminal ,Color:White	1	EA																																							
② C13, Color:black PVC 55P	0.0245	Kg																																							
① SJT 16AWGX3C 105°C,Color:black L=4980mm	1	EA																																							
G	<p style="text-align: center;">ROHS compliant Unit: mm</p> <table border="1"> <tr> <td>Scale</td> <td>Free</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="2">TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>① Add the current rating&voltage</td> <td>13.03.2017</td> <td>Winnie</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>② Drawn</td> <td>22.02.2017</td> <td>Winnie</td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id:</td> <td></td> <td></td> <td></td> <td></td> </tr> </table> <p>Customer-No. ASSMANN WSW-No. A-PC0916-500027 Drawing-No. ASS 7902 CA rev01 Replace Sheet</p>						Scale	Free						TOLERANCE							DIM	TOL	① Add the current rating&voltage	13.03.2017	Winnie					② Drawn	22.02.2017	Winnie			Angle	TOL	Id:				
Scale	Free																																								
TOLERANCE																																									
DIM	TOL	① Add the current rating&voltage	13.03.2017	Winnie																																					
		② Drawn	22.02.2017	Winnie																																					
Angle	TOL	Id:																																							
H	<p style="text-align: center;">ASSMANN components</p>																																								
1	2	3	4	5	6	7																																			
<p style="text-align: center;">ASSMANN components</p>						CABOT																																			