



Notes:

1. Insertion Loss: <0.3dB.
2. Return Loss: > 20dB.
3. Fiber Extension: -100nm <H<+100nm.
4. Ferrule End-Face Radius: 10<R<25mm.
5. Apex Offset: ≤50um.
6. Increase in insertion loss after 500 mating: 0.2dB Max.
7. Operation Temperature: -40°C to +75°C.
8. Storage Temperature: -40°C to +80°C.

WSW PN	Length
DK-2612-01	1m
DK-2612-02	2m
DK-2612-03	3m
DK-2612-05	5m
DK-2612-07	7m
DK-2612-10	10m

No.	Specifications	Qty
1	2.8x5.7mm OM1 62.5/125 Duplex Cable / LSZH / Orange	1
2	3.0mm SC/PC MM Connector / Beige	2
3	SC Duplex Clip / Beige	1
4	SC 3.0mm Boot / Black	1
5	SC 3.0mm Boot / Red	1
6	Tail Identification Marker (C-Clip)/ NO. A1, A2, B1, B2	4
7	Heat shrink Tube / Black	2
8	3.0mm ST / PC MM Connector / Silver	2
9	ST 3.0mm Boot / Black	1
10	ST 3.0mm Boot / Red	1

RoHS compliant
Unit: mm

Scale	Free				Date	Name	Customer-No.
TOLERANCE				Drawn	19.08.2019	Segal	ASSMANN WSW-No. DK-2612-xx
				Approved	19.08.2019	Segal	
DIM	TOL						Drawing-No. ASS 8611 CA
							rev00
Angle	TOL	Id.	Modification	Date	Name	Replace	Sheet



1

2

3

4

5

6

7