

A

B

Panel Thickness
Screw L=5.0 For Panel Thickness Under 1.2mm
Screw L=6.0 For Panel Thickness Between 1.2-2.0mm

C

Recommended Panel Cut-Out

D

E

A

P/N: ASCW-000-01EB11
 Length: 6mm
 P/N: ASCW-000-01EB10
 Length: 5mm
 Qty: 60pcs

B

Description:

- Test conditions:
 - Contact Resistance: 20mΩ Max;
 - Insulation Resistance: 500MΩ Min,DC 500V;
 - Medium Withstand Voltage: AC 500V, 1 minute;
 - 100% open, short circuit test.
- Rated Current: 2A;
- Durability life: 500 times;
- Protection Level: connector IP67;
- Applicable cable: 22AWG to 26AWG;
- Temperature Range: -40°C to +85°C.

9	Terminal Female, Ø1.1mm, connect area 1u" gold plating	9	PCS
8	Copper Alloy	1	PCS
7	Epoxy resin	4	G
6	Label L*W=50*20mm	1/30	PCS
5	PE Bag 60*90*0.04mm	1/30	PCS
4	Screws 4.75*11.0mm, 4#40	2	PCS
3	Screws 4.75*10.0mm, 4#40	2	PCS
2	Ring with DB series plastic frame small blue SIL45	1	PCS
1	DB series plastic frame small model (PA66+GF black) -40°C to+85°C	1	PCS
ITEMS	SPECIFICATION	Q'TY	UNIT

G	RoHS compliant Unit:mm	Scale	Free					Date	Name	Description: 9 Pin Waterproof DSub Female / IP67	G		
		TOLERANCE						Drawn	11.06.2020			Segal	
		.X	±0.25					Approved	11.06.2020			Segal	ASSMANN WSW-No.
H		DIM	TOL							A-DF09-GG-AU1-HB50	H		
		.X°	±1.0°							Drawing-No.		ASS 8614 CO	rev00
		X.°	±2.0°	©	Drawn	11.06.2020	Segal	ASSMANN WSW components		Customer-No.			
		Angle	TOL	Id.	Modification	Date	Name					SHEET 1 / 1	