

1 2 3 4 5 6 7

A B C D E F

SECTION VIEW:A-A

NOTES:

ELECTRICAL:

- VOLTAGE RATING:125 VAC;
- CURRENT RATING:1.5 AMP;
- CONTACT RESISTANCE:100 mΩ MAX;
- INSULATION RESISTANCE:1000 MΩ MIN @ 500 VDC;
- DIELECTRIC STRENGTH:750 VAC 60Hz, 1 MINUTE.

MATERIAL:

- HOUSING:PC UL94V-0;
- INSERT:GLASS FILLED POLYESTER UL94V-0 BK;
- PCB:FR-4 THICKNESS 1.6mm;
- CONTACT:PHOSPHOR BRONZE STAMP PIN t=0.35mm, 50u" GOLD PLATED;
- SHIELD:COPPER ALLOY 0.25mm THICKNESS NICKEL PLATING.

ENVIRONMENTAL:

- STORAGE:-40°C TO +85°C;
- OPERATION:0°C TO 70°C;

CONFORMING TO TIA/EIA 568B.2-1;
MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

PACKING:PE BAG.

Order Code:A-MJA-8-EG-L0B-Sx

1 = CAT6
2 = CAT5e

G H

RoHS compliant

Unit:mm

Scale	Free										
TOLERANCE											
X.X	±0.20										
X.XX	±0.15										
X.XXX	±0.10	②	Update the dimensions and tolerance	01.03.2022	Peter						
DIM	TOL	①	Update the dimensions and tolerance	17.03.2021	Segal						
X°	±5°	①	Drawn	06.01.2021	Segal						
Angle	TOL	Id.	Modification	Date	Name						

									Date	Name	Description: Keystone Jack shielded
								Drawn	06.01.2021	Segal	
								Approved	01.03.2022	Peter	ASSMANN WSW-No.
											A-MJA-8-EG-L0B-Sx
											Drawing-No.
											ASS 8810 CO
											rev02
											Customer-No.
											SHEET 1 / 1

1 2 3 4 5 6 7

SV5007