

1

2

3

4

5

6

7

A

B

C

D

E

F

A

B

C

D

E

F

G

H

NOTE:

1.MATERIAL

1.1 Contact:C5191,Gold flash over Nickel

2.ELECTRIC

2.1 Contact Resistance: 30 Mliohms Max

2.2 Insulation Resistance: 1000 Mega ohms Min

2.3 Dielectric Voltage: 500 V AC one Sec Level

① 2.4 Current Rating:1.5A DC

① 2.5 Voltage Rating:12V DC

3. Operating Temperature: -55°C To +105°C

4.Packing:Tape & Reel

Scale:2:1

PCB Layout Diagram

Top View

RoHS compliant

unit:mm

Scale Free

TOLERANCE

.X ±0.35

.X ±0.25

.XX ±0.20

.XXX ±0.15

DIM TOL

Angle TOL

①

Updated the note

03.11.2022

Peter

②

Drawn

24.11.2021

Peter

Id.

modification

Date

Name

Date

Name

Description: Battery Contacts
Type: AA / AAA / LR03 / LR06

Drawn

24.11.2021

Peter

Approved

03.11.2022

Peter

ASSMANN WSW-NO.

A-BAT-BH-B0-EA-GSR1

Drawing-No.

ASS 9094 CO

rev01

Customer-No.

SHEET
1 / 1

1

2

3

4

5

6

7

SV5043