



PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 03.03.2022
MODIFICATION / REVISION DATE: 03.03.2022

AKSNT/x BLACK Jumper Connector

CHANGE NOTIFICATION:

PCN 20220303_AKSNTxBLACK

DESCRIPTION OF CHANGES:

CHANGE OF PRODUCT LOCATION
CHANGE OF DATA SHEET
New Draw.-No. ASS_1004_COrev04

REASON FOR CHANGE:

CHANGE OF PRODUCT LOCATION
CHANGE OF PRODUCT DIMENSIONS, TOLERANCES AND/OR PROPERTIES

KEY CHARACTERISTICS OF CHANGE:

Details see page 3

PRODUCTS AFFECTED:

AKSNT/x BLACK

DATE OF CHANGE AND IMPLEMENTATION:

CHANGE: WEEK 10 / YEAR 2022
IMPLEMENTATION: 03.03.2022

RESPONSE:

NO RESPONSE TO THIS NOTIFICATION IS REQUIRED



PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 03.03.2022
MODIFICATION / REVISION DATE: 03.03.2022

REFERENCE DOCUMENTS / ATTACHMENTS:
DOCUMENT: DRAWING

ASSMANN WSW P/N	Drawing Number		ASSMANN WSW P/N	Drawing Number
AKSNT/x BLACK	ASS_1004_CO rev03	↔	AKSNT/x BLACK	ASS_1004_co rev04



Auf dem Schüffel 1
 D-58513 Lüdenscheid
 Tel.: +49-2351 - 554-200
 Fax +49 (2351) 554-861
 info@assmann-wsw.com
 www.assmann-wsw.com

PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 03.03.2022
 MODIFICATION / REVISION DATE: 03.03.2022

AKSNT/x BLACK	OLD VERSION	AKSNT/x BLACK	NEW VERSION
<p>NOTES:</p> <ol style="list-style-type: none"> 1. Insulation: 30% Glass Filled PBT, UL94V-0, Color Black 2. Contact : Brass 3. Current Rating: 3A Max 4. Dielectric Voltage: 1000V rms / 1 minute 5. Insulation Resistance: 1000M ohm Min. 6. Contact Resistance: 30m ohm Max. 7. Operating and Storage Temperature: -40°C ~ +105°C 8. MatInq Cycles: 10 Min. <p>AKSNT/x BLACK</p> <p>— Contact Area Plating: ③ G: Gold Flash Z: Tinned</p>	<p>NOTES:</p> <ol style="list-style-type: none"> 1. Insulator: PBT+30% G.F,UL94V-0,Black 2. Contact : Phosphor Bronze,Au or Sn over Ni 3. Current Rating: 3.0AMP 4. Dielectric Withstanding Voltage: 1000V AC/ minute 5. Insulation Resistance: 500MΩ Min. 6. Contact Resistance: 20mΩ Max. 7. Operating Temperature: -40°C ~ +105°C <p>③ AKSNT/x BLACK</p> <p>— Contact Area Plating: ③ G: Gold Flash Z: Tinned</p> <p>SECTION A-A</p>		
FOR DETAIL, PLEASE TAKE ATTACHED NEW DRAWING: FOR REFERENCE			

	1	2	3	4	5	6	7						
A							<p>NOTES:</p> <p>1. Insulator: PBT+30% G.F, UL94V-0, Black</p> <p>④ 2. Contact : Phosphor Bronze, Au or Sn over Ni</p> <p>3. Current Rating: 3.0AMP</p> <p>4. Dielectric Withstanding Voltage: 1000V AC/ minute</p> <p>④ 5. Insulation Resistance: 500MΩ Min.</p> <p>④ 6. Contact Resistance: 20mΩ Max.</p> <p>7. Operating Temperature: -40°C ~ +105°C</p> <p>③ AKSNT/x BLACK</p> <p> Contact Area Plating: ③</p> <p> G: Gold Flash</p> <p> Z: Tinned</p>		A				
B									B				
C									C				
D									D				
E							<p>SECTION A-A</p>		E				
F									F				
G	<p>RoHS compliant Unit:mm</p>		Scale	Free				Date	Name	Customer-No.	G		
			TOLERANCE					Drawn	03.03.2004	Hellwig			
			X.	±0.35	④	Update the dimension and tolerance	02.03.2022	Peter	Approved	02.03.2022		Peter	ASSMANN WSW-No. AKSNT/G BLACK AKSNT/Z BLACK
			X.X	±0.25	③	Update	07.06.2013	Winnie					
			X.XX	±0.20	②	Update	27.07.2009	Rale				Drawing-No.	
			X.XXX	±0.15	①	Update	03.03.2004	Hellwig				ASS 1004 CO	rev04
H					Angle	TOL	Id.	Modification	Date	Name		Replace	SHEET 1 / 1
	1	2	3	4	5	6	7						