

Auf dem Schüffel 1
D-58513 Lüdenscheid
Tel.: +49-2351 - 5542-00
Fax +49 (2351) 554-861
info@assmann-wsw.com
www.assmann-wsw.com

PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 22.01.2024
MODIFICATION / REVISION DATE: 22.01.2024

A-M12AxxMOExxxx2BK00 Circular cable/M12 A-Coding male to open

CHANGE NOTIFICATION: PCN 20240122_A-M12AxxMOExxxx2BK00

DESCRIPTION OF CHANGES: CHANGE OF DATA SHEET
CHANGE OF DATA SHEET
New Draw.-ASS_8414_CArev04

REASON FOR CHANGE: CHANGE OF PRODUCT DIMENSIONS, TOLERANCES AND/OR PROPERTIES
CHANGE OF PRODUCT DIMENSIONS, TOLERANCES AND/OR PROPERTIES

KEY CHARACTERISTICS OF CHANGE: Details see page 3

PRODUCTS AFFECTED: A-M12AxxMOExxxx2BK00

DATE OF CHANGE AND IMPLEMENTATION: CHANGE: 04/2024
IMPLEMENTATION: 22.01.2024

RESPONSE: NO RESPONSE TO THIS NOTIFICATION IS REQUIRED

PCN REVISION HISTORY:

DATE OF REVISION: 22.01.2024

REVISION NUMBER: 00

page 1/

Auf dem Schöffel 1
D-58513 Lüdenscheid
Tel.: +49-2351 - 554-200
Fax +49 (2351) 554-861
info@assmann-wsw.com
www.assmann-wsw.com

PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 22.01.2024
MODIFICATION / REVISION DATE: 22.01.2024

A-M12AxxMOExxx2BK00	OLD VERSION	A-M12AxxMOExxx2BK00	NEW VERSION																																								
1. Notes.		1. Notes.																																									
Notes:		Notes: ④																																									
Detailed Product Description:		Detailed Product Description:																																									
1. Waterproof connector rating is IP67/IP68		1. Waterproof connector rating is IP67																																									
2. Outer Jacket material : PUR Black		2. Outer Jacket material : PUR Black																																									
3. Protected from dust and water during immersion, resistant to many oils and chemical etc.		3. Protected from dust and water during immersion resistant to many oils and chemical etc.																																									
4. Insulation Resistance: >100MΩ.		4. Insulation Resistance: >100MΩ.																																									
5. Contact Resistance of connector: ≤10mΩ.		5. Contact Resistance of connector: ≤10mΩ.																																									
6. Operating temperature: -25°C ~ +85°C.		6. Operating temperature: -25°C ~ +80°C.																																									
2. Item 3# in BOM		2. Item 3# in BOM																																									
<table border="1"> <thead> <tr> <th>ITEM</th> <th>SPECIFICATION</th> <th>Q'TY</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>④</td> <td>BLACK PUR</td> <td>6</td> <td>G</td> </tr> <tr> <td>③</td> <td>HD PE</td> <td>3</td> <td>G</td> </tr> <tr> <td>②</td> <td>M12 A CODING FEMALE CONNECTOR</td> <td>1</td> <td>SET</td> </tr> <tr> <td>①</td> <td>UL20549 JACKET BLACK PUR</td> <td>1</td> <td>PCS</td> </tr> </tbody> </table>	ITEM	SPECIFICATION	Q'TY	UNIT	④	BLACK PUR	6	G	③	HD PE	3	G	②	M12 A CODING FEMALE CONNECTOR	1	SET	①	UL20549 JACKET BLACK PUR	1	PCS		<table border="1"> <thead> <tr> <th>ITEM</th> <th>SPECIFICATION</th> <th>Q'TY</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>④</td> <td>BLACK PUR</td> <td>6</td> <td>G</td> </tr> <tr> <td>③</td> <td>Amber Low Pressure Injection Compound ④</td> <td>3</td> <td>G</td> </tr> <tr> <td>②</td> <td>M12 A CODING FEMALE CONNECTOR</td> <td>1</td> <td>SET</td> </tr> <tr> <td>①</td> <td>UL20549 JACKET BLACK PUR</td> <td>1</td> <td>PCS</td> </tr> </tbody> </table>	ITEM	SPECIFICATION	Q'TY	UNIT	④	BLACK PUR	6	G	③	Amber Low Pressure Injection Compound ④	3	G	②	M12 A CODING FEMALE CONNECTOR	1	SET	①	UL20549 JACKET BLACK PUR	1	PCS	
ITEM	SPECIFICATION	Q'TY	UNIT																																								
④	BLACK PUR	6	G																																								
③	HD PE	3	G																																								
②	M12 A CODING FEMALE CONNECTOR	1	SET																																								
①	UL20549 JACKET BLACK PUR	1	PCS																																								
ITEM	SPECIFICATION	Q'TY	UNIT																																								
④	BLACK PUR	6	G																																								
③	Amber Low Pressure Injection Compound ④	3	G																																								
②	M12 A CODING FEMALE CONNECTOR	1	SET																																								
①	UL20549 JACKET BLACK PUR	1	PCS																																								
FOR DETAIL, PLEASE TAKE ATTACHED NEW DRAWING: ASS_1570_COrev09 FOR REFERENCE																																											

PCN REVISION HISTORY:

DATE OF REVISION: 22.01.2024

REVISION NUMBER: 00