



PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 26.04.2021
MODIFICATION / REVISION DATE: 26.04.2021

A-DVI-24-D DVI CONNECTOR

CHANGE NOTIFICATION:

PCN-20210426-ADVI24D

DESCRIPTION OF CHANGES:

CHANGE OF DATA SHEET
CHANGE OF PRODUCT DESIGN
New Draw.-No. ASS 3271 COrev02

REASON FOR CHANGE:

CHANGE OF PRODUCT DIMENSIONS, TOLERANCES
CHANGE OF KEY PRODUCT DESIGN PARAMETERS

KEY CHARACTERISTICS OF CHANGE:

Details see page 3

PRODUCTS AFFECTED:

A-DVI-24D
DVI CONNECTOR / MALE

DATE OF CHANGE AND IMPLEMENTATION:

CHANGE: WEEK 17 / YEAR 2021
IMPLEMENTATION: 26.04.2021

RESPONSE:

NO RESPONSE TO THIS NOTIFICATION IS REQUIRED

PCN REVISION HISTORY:

DATE OF REVISION: 26.04.2021

REVISION NUMBER: 00



Auf dem Schöffel 1
D-58513 Lüdenscheid
Tel.: +49-2351 - 554-200
Fax +49 (2351) 554-861
info@assmann-wsw.com
www.assmann-wsw.com

PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: [26.04.2021](#)
MODIFICATION / REVISION DATE: [26.04.2021](#)

REFERENCE DOCUMENTS / ATTACHMENTS:
DOCUMENT: DRAWING

ASSMANN WSW P/N	Drawing Number		ASSMANN WSW P/N	Drawing Number
A-DVI-24D	ASS_3271_COrev01		A-DVI-24D	ASS_3271_COrev02



Auf dem Schüffel 1
 D-58513 Lüdenscheld
 Tel.: +49-2351 - 554-200
 Fax +49 (2351) 554-861
 info@assmann-wsw.com
 www.assmann-wsw.com

PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 26.04.2021
 MODIFICATION / REVISION DATE: 26.04.2021

A-DVI-24-D OLD VERSION	A-DVI-24D NEW VERSION																												
<table border="1" style="margin-top: 20px; width: 100%;"> <tr><td>Scale</td><td>1:1</td></tr> <tr><td colspan="2">TOLERANCE</td></tr> <tr><td>X.</td><td>±0.38</td></tr> <tr><td>X.X</td><td>±0.25</td></tr> <tr><td>X.XX</td><td>±0.13</td></tr> <tr><td>DIM</td><td>TOL</td></tr> <tr><td>X.°</td><td>±3°</td></tr> </table> <p>2.MATERIAL: Insulator Material: Glass-filled thermoplastic Natural Contact Material: Phosphor Bronze Shell :SPCC or ZINC Alloy, Nickel Over Cu Plated Board lock : Brass Tin Plated</p>	Scale	1:1	TOLERANCE		X.	±0.38	X.X	±0.25	X.XX	±0.13	DIM	TOL	X.°	±3°	<table border="1" style="margin-top: 20px; width: 100%;"> <tr><td>Scale</td><td>1:1</td></tr> <tr><td colspan="2">TOLERANCE</td></tr> <tr><td>X.</td><td>±0.50</td></tr> <tr><td>X.X</td><td>±0.38</td></tr> <tr><td>X.XX</td><td>±0.25</td></tr> <tr><td>DIM</td><td>TOL</td></tr> <tr><td>X.°</td><td>±3°</td></tr> </table> <p>2.MATERIAL: Insulator Material: Glass-filled thermoplastic Natural Contact Material: Brass Gold flash on contact area Shell :SPCC Sn plated over Nickel Board lock : Brass Tin Plated</p>	Scale	1:1	TOLERANCE		X.	±0.50	X.X	±0.38	X.XX	±0.25	DIM	TOL	X.°	±3°
Scale	1:1																												
TOLERANCE																													
X.	±0.38																												
X.X	±0.25																												
X.XX	±0.13																												
DIM	TOL																												
X.°	±3°																												
Scale	1:1																												
TOLERANCE																													
X.	±0.50																												
X.X	±0.38																												
X.XX	±0.25																												
DIM	TOL																												
X.°	±3°																												
FOR DETAIL, PLEASE TAKE ATTACHED NEW DRAWING: FOR REFERENCE																													

PCN REVISION HISTORY:

DATE OF REVISION: 26.04.2021

REVISION NUMBER: 00

	1	2	3	4	5	6	7																																																																														
A								A																																																																													
B								B																																																																													
C								C																																																																													
D								D																																																																													
E								E																																																																													
F								F																																																																													
G	RoHS compliant		<table border="1"> <tr> <td>Scale</td> <td>1:1</td> <td></td> <td></td> <td></td> <td></td> <td>Date</td> <td>Name</td> <td colspan="2">Description</td> </tr> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>29.12.2008</td> <td>Dean</td> <td rowspan="4">ASSMANN WSW-No. A-DVI-24D</td> </tr> <tr> <td>X.</td> <td>±0.50</td> <td></td> <td></td> <td></td> <td></td> <td>Approved</td> <td>26.04.2021</td> <td>Daniel</td> </tr> <tr> <td>X.X</td> <td>±0.38</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±0.25</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>②</td> <td>Update</td> <td>26.04.2021</td> <td>Daniel</td> <td colspan="2" rowspan="3"> </td> <td>Drawing-No.</td> <td rowspan="2">ASS 3271 CO</td> </tr> <tr> <td>X.°</td> <td>±3°</td> <td>①</td> <td>Drawn</td> <td>29.12.2008</td> <td>Dean</td> <td>rev02</td> </tr> <tr> <td>X.X°</td> <td>±1°</td> <td></td> <td></td> <td></td> <td></td> <td>Customer-No.</td> <td>Sheet</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> <td></td> <td>1/1</td> </tr> </table>	Scale	1:1					Date	Name	Description		TOLERANCE						Drawn	29.12.2008	Dean	ASSMANN WSW-No. A-DVI-24D	X.	±0.50					Approved	26.04.2021	Daniel	X.X	±0.38								X.XX	±0.25								DIM	TOL	②	Update	26.04.2021	Daniel			Drawing-No.	ASS 3271 CO	X.°	±3°	①	Drawn	29.12.2008	Dean	rev02	X.X°	±1°					Customer-No.	Sheet	Angle	TOL	Id.	Modification	Date	Name			1/1	G
Scale	1:1					Date	Name	Description																																																																													
TOLERANCE						Drawn	29.12.2008	Dean	ASSMANN WSW-No. A-DVI-24D																																																																												
X.	±0.50					Approved	26.04.2021	Daniel																																																																													
X.X	±0.38																																																																																				
X.XX	±0.25																																																																																				
DIM	TOL	②	Update	26.04.2021	Daniel			Drawing-No.	ASS 3271 CO																																																																												
X.°	±3°	①	Drawn	29.12.2008	Dean			rev02																																																																													
X.X°	±1°							Customer-No.	Sheet																																																																												
Angle	TOL	Id.	Modification	Date	Name			1/1																																																																													
H									H																																																																												
	1	2	3	4	5	6	7																																																																														

NOTES:

- 1.ENVIRONMENTAL:
Temperature Range : -20°C To +80°C
- 2.MATERIAL:
Insulator Material:Glass-filled thermoplastic Natural,UL94V-0
Contact Material: Brass ,Gold flash on contact area
Shell :SPCC , Sn plated over Nickel
Board lock : Brass Tin Plated
- 3.ELECTRICAL
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ min
Withstand Voltage: 500V AC(ms)
- 4.MECHANICAL
Mating force : 10 LB.(4.5Kg) Max
Unmating Force :2.2LB.(1Kg) Min .8.8LB.(4Kg)Max.

