



PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 20.04.2022
MODIFICATION / REVISION DATE: 20.04.2022

AKSCTx xx
Jumper Connector

CHANGE NOTIFICATION:

PCN_20220420_AKSCTxxx

DESCRIPTION OF CHANGES:

CHANGE OF PRODUCT LOCATION
CHANGE OF DATA SHEET
New Draw.-No.ASS_0591_COrev05

REASON FOR CHANGE:

CHANGE OF PRODUCT LOCATION
CHANGE OF PRODUCT DIMENSIONS, TOLERANCES AND/OR PROPERTIES

KEY CHARACTERISTICS OF CHANGE:

Details see page 3

PRODUCTS AFFECTED:

AKSCTx xx

DATE OF CHANGE AND IMPLEMENTATION:

CHANGE: WEEK 17 / YEAR 2022
IMPLEMENTATION: 2022-04-20

RESPONSE:

NO RESPONSE TO THIS NOTIFICATION IS REQUIRED



Auf dem Schöffel 1
D-58513 Lüdenscheid
Tel.: +49-2351 - 554-200
Fax +49 (2351) 554-861
info@assmann-wsw.com
www.assmann-wsw.com

PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 20.04.2022
MODIFICATION / REVISION DATE: 20.04.2022

REFERENCE DOCUMENTS / ATTACHMENTS:
DOCUMENT: DRAWING

ASSMANN WSW P/N	Drawing Number		ASSMANN WSW P/N	Drawing Number
AKSCTx xx	ASS_0591_COrev04	↔	AKSCTx xx	ASS_0591_COrev05
AKSCT/G BLUE	ASS_0591_COrev04	↔	Discontinue	Discontinue
AKSCT/Z BLUE	ASS_0591_COrev04	↔	Discontinue	Discontinue



Auf dem Schüffel 1
 D-58513 Lüdenscheid
 Tel.: +49-2351 - 554-200
 Fax +49 (2351) 554-861
 info@assmann-wsw.com
 www.assmann-wsw.com

PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 20.04.2022
 MODIFICATION / REVISION DATE: 20.04.2022

AKSCTx xx OLD VERSION	AKSCTx xx NEW VERSION																																				
<table border="1" style="margin-top: 10px; width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Scale</th> <th>Free</th> </tr> </thead> <tbody> <tr> <td colspan="2" style="text-align: center;">TOLERANCE</td> </tr> <tr> <td>.X</td> <td>±0.38</td> </tr> <tr> <td>.XX</td> <td>±0.25</td> </tr> <tr> <td>.XXX</td> <td>±0.13</td> </tr> <tr> <td>DIM</td> <td>TOL</td> </tr> <tr> <td>X.°</td> <td>±1°</td> </tr> <tr> <td>Angle</td> <td>TOL</td> </tr> <tr> <td>UNIT</td> <td>mm</td> </tr> </tbody> </table>	Scale	Free	TOLERANCE		.X	±0.38	.XX	±0.25	.XXX	±0.13	DIM	TOL	X.°	±1°	Angle	TOL	UNIT	mm	<table border="1" style="margin-top: 10px; width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Scale</th> <th>Free</th> </tr> </thead> <tbody> <tr> <td colspan="2" style="text-align: center;">TOLERANCE</td> </tr> <tr> <td>.X</td> <td>±0.38</td> </tr> <tr> <td>.XX</td> <td>±0.25</td> </tr> <tr> <td>.XXX</td> <td>±0.15</td> </tr> <tr> <td>DIM</td> <td>TOL</td> </tr> <tr> <td>X.°</td> <td>±1°</td> </tr> <tr> <td>Angle</td> <td>TOL</td> </tr> <tr> <td>UNIT</td> <td>mm</td> </tr> </tbody> </table>	Scale	Free	TOLERANCE		.X	±0.38	.XX	±0.25	.XXX	±0.15	DIM	TOL	X.°	±1°	Angle	TOL	UNIT	mm
Scale	Free																																				
TOLERANCE																																					
.X	±0.38																																				
.XX	±0.25																																				
.XXX	±0.13																																				
DIM	TOL																																				
X.°	±1°																																				
Angle	TOL																																				
UNIT	mm																																				
Scale	Free																																				
TOLERANCE																																					
.X	±0.38																																				
.XX	±0.25																																				
.XXX	±0.15																																				
DIM	TOL																																				
X.°	±1°																																				
Angle	TOL																																				
UNIT	mm																																				
FOR DETAIL, PLEASE TAKE ATTACHED NEW DRAWING: FOR REFERENCE																																					

PCN REVISION HISTORY:


DATE OF REVISION: 20.04.2022

REVISION NUMBER: 00

	1	2	3	4	5	6	7																																																																																				
A								A																																																																																			
B								B																																																																																			
C								C																																																																																			
D								D																																																																																			
E								E																																																																																			
F								F																																																																																			
G	RoHS compliant Unit:mm							G																																																																																			
H	<table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th></th> <th></th> <th></th> <th></th> <th>Date</th> <th>Name</th> <th>Customer-No.</th> </tr> </thead> <tbody> <tr> <td colspan="2">TOLERANCE</td> <td>⑤</td> <td>Change the plant</td> <td>20.04.2022</td> <td>Winnle</td> <td>Drawn</td> <td>10.04.2002</td> <td>Hellwlg</td> </tr> <tr> <td>.X</td> <td>±0,38</td> <td>④</td> <td>Update</td> <td>07.06.2013</td> <td>Winnle</td> <td>Approved</td> <td>20.04.2022</td> <td>Winnle</td> </tr> <tr> <td>.XX</td> <td>±0,25</td> <td>③</td> <td>Update</td> <td>21.11.2012</td> <td>Amy</td> <td></td> <td></td> <td></td> </tr> <tr> <td>.XXX</td> <td>±0.15</td> <td>②</td> <td>Update</td> <td>27.07.2009</td> <td>Rale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>①</td> <td>Drawn</td> <td>10.04.2002</td> <td>Hellwlg</td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.°</td> <td>±1°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>UNIT</td> <td>mm</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>			Scale	Free					Date	Name	Customer-No.	TOLERANCE		⑤	Change the plant	20.04.2022	Winnle	Drawn	10.04.2002	Hellwlg	.X	±0,38	④	Update	07.06.2013	Winnle	Approved	20.04.2022	Winnle	.XX	±0,25	③	Update	21.11.2012	Amy				.XXX	±0.15	②	Update	27.07.2009	Rale				DIM	TOL	①	Drawn	10.04.2002	Hellwlg				X.°	±1°								Angle	TOL								UNIT	mm	Id.	Modification	Date	Name										H
Scale	Free					Date	Name	Customer-No.																																																																																			
TOLERANCE		⑤	Change the plant	20.04.2022	Winnle	Drawn	10.04.2002	Hellwlg																																																																																			
.X	±0,38	④	Update	07.06.2013	Winnle	Approved	20.04.2022	Winnle																																																																																			
.XX	±0,25	③	Update	21.11.2012	Amy																																																																																						
.XXX	±0.15	②	Update	27.07.2009	Rale																																																																																						
DIM	TOL	①	Drawn	10.04.2002	Hellwlg																																																																																						
X.°	±1°																																																																																										
Angle	TOL																																																																																										
UNIT	mm	Id.	Modification	Date	Name																																																																																						
	1	2	3	4	5	6	7																																																																																				

NOTES:

- 1. Insulation: Glass Filled PBT, UL94V-0, Color Black/Red/Blue
- 2. Contact : Phorphos Bronze
- 3. Current Rating: 3A Max
- 4. Dielectric Voltage: 1000V rms / 1 minute
- 5. Insulation Resistance: 1000M ohm Min.
- 6. Contact Resistance: 30m ohm Max.
- 7. Operating and Storage Temperature: -40°C ~ +105°C
- ④ 8. Mating Cycles: 10 Min.



ASSMANN WSW-No.	AKSCT/G X AKSCT/Z X
Drawing-No.	ASS 0591 CO
Replace	rev05
	SHEET